



Association for Standardisation of
Automation and Measuring Systems

ASAM MCD-2 MC (ASAP2 / A2L)

Data Model for ECU Measurement and
Calibration

Version 1.7.1

Date: 2018-01-30

Base Standard

© by ASAM e.V., 2018

Disclaimer

This document is the copyrighted property of ASAM e.V.
Any use is limited to the scope described in the license terms. The license terms can be viewed at www.asam.net/license

Table of Contents

Foreword	9
1 Introduction	10
1.1 Overview	10
1.2 Motivation	10
1.3 Scope	10
1.4 History	11
2 Relations to Other Standards	12
2.1 Backward Compatibility to Earlier Releases	12
2.1.1 Incompatibility of Keyword FORMULA	12
2.1.2 Restriction for Brackets	13
2.1.3 Win32 APIs for Seed&Key and Checksum Calculation	13
2.1.4 Optional numbers for MATRIX_DIM	13
2.2 References to Other Standards	13
2.2.1 ASAM MCD-2 MC within the ASAM AE Overall Context	13
2.2.2 ASAM MCD-1	14
2.2.3 ASAM MCD-2	14
2.2.3.1 ASAM MCD-2 D ODX	15
2.2.3.2 ASAM MCD-2 NET	15
2.2.4 ASAM MCD-3	15
2.2.5 More ASAM Standards with an ASAM MCD-2 MC relation	15
3 Division of the description data	16
4 Format of the description file	18
4.1 Encoding of the A2L file	18
4.1.1 Unicode Transformation Format	18
4.1.2 Byte-Order Mark	18
4.1.3 Whitespace definition	18
4.2 Hierarchic division of the keywords	20
4.3 Name Spaces	29
4.3.1 Functions	29
4.3.2 Groups	29
4.3.3 Variants	29
4.3.4 Measure and adjustable objects	29
4.3.5 Transformer	29
4.3.6 Conversion methods	29
4.3.7 Conversion tables	29
4.3.8 Memory segments	29
4.3.9 Record layouts	30
4.3.10 Type definitions	30
4.3.11 Structure components	30
4.4 Predefined data types	30

4.5	Mapping of predefined data Types to ASAM data types.....	33
4.6	Comments.....	33
4.7	Alphabetical list of keywords	34
4.7.1	General.....	34
4.7.2	A2ML.....	35
4.7.3	A2ML_VERSION	36
4.7.4	ADDR_EPK	37
4.7.5	ADDRESS_TYPE	38
4.7.6	ALIGNMENT_BYTE.....	39
4.7.7	ALIGNMENT_FLOAT16_IEEE	40
4.7.8	ALIGNMENT_FLOAT32_IEEE	41
4.7.9	ALIGNMENT_FLOAT64_IEEE	42
4.7.10	ALIGNMENT_INT64	43
4.7.11	ALIGNMENT_LONG.....	44
4.7.12	ALIGNMENT_WORD.....	45
4.7.13	ANNOTATION	46
4.7.14	ANNOTATION_LABEL	47
4.7.15	ANNOTATION_ORIGIN.....	48
4.7.16	ANNOTATION_TEXT	49
4.7.18	ARRAY_SIZE	50
4.7.20	AR_COMPONENT	51
4.7.21	AR_PROTOTYPE_OF.....	53
4.7.22	ASAP2_VERSION	54
4.7.24	AXIS_DESCR.....	55
4.7.25	AXIS_PTS	59
4.7.26	AXIS_PTS_REF	63
4.7.27	AXIS_PTS_X / _Y / _Z / _4 / _5.....	65
4.7.28	AXIS_RESCALE_X	66
4.7.29	BIT_MASK.....	68
4.7.30	BIT_OPERATION	69
4.7.31	BLOB.....	70
4.7.32	BYTE_ORDER	72
4.7.33	CALIBRATION_ACCESS	74
4.7.34	CALIBRATION_HANDLE	75
4.7.35	CALIBRATION_HANDLE_TEXT.....	76
4.7.36	CALIBRATION_METHOD.....	77
4.7.37	CHARACTERISTIC	78
4.7.38	COEFFS.....	84
4.7.39	COEFFS_LINEAR	85
4.7.41	COMPARISON_QUANTITY	86
4.7.42	COMPU_METHOD.....	87
4.7.43	COMPU_TAB	91
4.7.44	COMPU_TAB_REF	93
4.7.45	COMPU_VTAB.....	94
4.7.46	COMPU_VTAB_RANGE	96
4.7.47	CONSISTENT_EXCHANGE	98
4.7.48	CONVERSION.....	99
4.7.49	CPU_TYPE.....	100
4.7.50	CURVE_AXIS_REF.....	101
4.7.51	CUSTOMER	103
4.7.52	CUSTOMER_NO.....	104
4.7.53	DATA_SIZE	105
4.7.54	DEF_CHARACTERISTIC	106

4.7.55	DEFAULT_VALUE.....	107
4.7.56	DEFAULT_VALUE_NUMERIC.....	108
4.7.57	DEPENDENT_CHARACTERISTIC.....	109
4.7.58	DEPOSIT.....	111
4.7.59	DISCRETE.....	112
4.7.60	DISPLAY_IDENTIFIER.....	113
4.7.61	DIST_OP_X / _Y / _Z / _4 / _5.....	114
4.7.62	ECU.....	115
4.7.63	ECU_ADDRESS.....	116
4.7.64	ECU_ADDRESS_EXTENSION.....	117
4.7.65	ECU_CALIBRATION_OFFSET.....	118
4.7.66	ENCODING.....	119
4.7.67	EPK.....	120
4.7.68	ERROR_MASK.....	121
4.7.69	EXTENDED_LIMITS.....	122
4.7.70	FIX_AXIS_PAR.....	123
4.7.71	FIX_AXIS_PAR_DIST.....	124
4.7.72	FIX_AXIS_PAR_LIST.....	125
4.7.73	FIX_NO_AXIS_PTS_X / _Y / _Z / _4 / _5.....	126
4.7.74	FNC_VALUES.....	127
4.7.75	FORMAT.....	130
4.7.76	FORMULA.....	131
4.7.77	FORMULA_INV.....	133
4.7.78	FRAME.....	134
4.7.79	FRAME_MEASUREMENT.....	136
4.7.80	FUNCTION.....	137
4.7.81	FUNCTION_LIST.....	139
4.7.82	FUNCTION_VERSION.....	140
4.7.83	GROUP.....	141
4.7.84	GUARD_RAILS.....	145
4.7.85	HEADER.....	146
4.7.86	IDENTIFICATION.....	147
4.7.87	IF_DATA (Example).....	148
4.7.88	IN_MEASUREMENT.....	149
4.7.89	INPUT_QUANTITY.....	150
4.7.90	INSTANCE.....	151
4.7.91	LAYOUT.....	155
4.7.92	LEFT_SHIFT.....	156
4.7.93	LIMITS.....	157
4.7.94	LOC_MEASUREMENT.....	158
4.7.95	MAP_LIST.....	159
4.7.96	MATRIX_DIM.....	160
4.7.97	MAX_GRAD.....	161
4.7.98	MAX_REFRESH.....	162
4.7.99	MEASUREMENT.....	163
4.7.100	MEMORY_LAYOUT.....	167
4.7.101	MEMORY_SEGMENT.....	169
4.7.102	MOD_COMMON.....	173
4.7.103	MOD_PAR.....	175
4.7.105	MODEL_LINK.....	177
4.7.106	MODULE.....	178
4.7.107	MONOTONY.....	180
4.7.108	NO_AXIS_PTS_X / _Y / _Z / _4 / _5.....	181
4.7.109	NO_OF_INTERFACES.....	182

4.7.110	NO_RESCALE_X	183
4.7.111	NUMBER	184
4.7.112	OFFSET_X / _Y / _Z / _4 / _5	185
4.7.113	OUT_MEASUREMENT	186
4.7.114	OVERWRITE	187
4.7.115	PHONE_NO	190
4.7.116	PHYS_UNIT	191
4.7.117	PROJECT	192
4.7.118	PROJECT_NO	193
4.7.119	READ_ONLY	194
4.7.120	READ_WRITE	195
4.7.121	RECORD_LAYOUT	196
4.7.122	REF_CHARACTERISTIC	202
4.7.123	REF_GROUP	203
4.7.124	REF_MEASUREMENT	204
4.7.125	REF_MEMORY_SEGMENT /DEPRECATED	205
4.7.126	REF_UNIT	206
4.7.127	RESERVED	207
4.7.128	RIGHT_SHIFT	208
4.7.129	RIP_ADDR_W / _X / _Y / _Z / _4 / _5	209
4.7.130	ROOT	211
4.7.131	SHIFT_OP_X / _Y / _Z / _4 / _5	212
4.7.132	SIGN_EXTEND	213
4.7.133	SI_EXPONENTS	214
4.7.134	SRC_ADDR_X / _Y / _Z / _4 / _5	215
4.7.135	STATIC_ADDRESS_OFFSETS	216
4.7.136	STATIC_RECORD_LAYOUT	217
4.7.137	STATUS_STRING_REF	219
4.7.138	STEP_SIZE	220
4.7.139	STRUCTURE_COMPONENT	221
4.7.140	SUB_FUNCTION	223
4.7.141	SUB_GROUP	224
4.7.142	SUPPLIER	225
4.7.143	SYMBOL_LINK	226
4.7.144	SYMBOL_TYPE_LINK	227
4.7.146	SYSTEM_CONSTANT	228
4.7.147	TRANSFORMER	229
4.7.148	TRANSFORMER_IN_OBJECTS	233
4.7.149	TRANSFORMER_OUT_OBJECTS	234
4.7.150	TYPEDDEF_AXIS	235
4.7.151	TYPEDDEF_BLOB	237
4.7.152	TYPEDDEF_CHARACTERISTIC	238
4.7.153	TYPEDDEF_MEASUREMENT	240
4.7.154	TYPEDDEF_STRUCTURE	242
4.7.155	UNIT	245
4.7.156	UNIT_CONVERSION	247
4.7.157	USER	248
4.7.158	USER_RIGHTS	249
4.7.159	VAR_ADDRESS	251
4.7.160	VAR_CHARACTERISTIC	252
4.7.161	VAR_CRITERION	253
4.7.162	VAR_FORBIDDEN_COMB	254
4.7.163	VAR_MEASUREMENT	255
4.7.164	VAR_NAMING	256

4.7.165 VAR_SELECTION_CHARACTERISTIC	257
4.7.166 VAR_SEPARATOR	258
4.7.167 VARIANT_CODING	259
4.7.168 VERSION	261
4.7.169 VIRTUAL	262
4.7.170 VIRTUAL_CHARACTERISTIC	263
5 Include mechanism	265
6 ASAM MCD-2 MC Metalanguage	266
6.1 General	266
6.2 Format of the ASAM MCD-2 MC metalanguage	268
6.3 Designing AML-file	273
7 Terms and Definitions	274
8 Symbols and Abbreviated Terms	275
9 Bibliography	276
Appendix: A. IEEE-Floating-Point-Format	277
A.1. 16-Bit Format	277
A.2. 32-Bit Format	277
A.3. 64-Bit Format	278
Appendix: B. Using Reference Curves as Normalization Axes for Maps	279
B.1. Background	279
B.1.1. General	279
B.1.2. Overall technique	279
B.1.3. Determining the map indices	279
B.1.4. Determining the map normalized value	279
B.2. Example	280
Appendix: C. Codes for scaling units (CSE)	282
Appendix: D. Transformer	284
D.1. Basics	284
D.2. Transformer DLL API definition and rules	286
D.2.1. General API description	286
D.2.2. Detailed C transformer API definition	287
D.2.2.1. Typedefs	287
D.2.2.2. IsTransformationPossible DLL Function	290
D.2.2.3. GetTransformerDescription DLL Function	291
D.2.2.4. GetDIIDescription DLL Function	292
D.2.2.5. ExecuteTransformation DLL Function	293

Appendix: E.	ASAP2 Container	294
E.1.	Container	294
E.2.	Common.....	294
E.3.	Category.....	295
E.4.	ABLOCK.....	296
E.5.	FILES.....	296
E.6.	AREF	296
E.7.	Example for Container Catalog File	297
Appendix: F.	Formulas	302
F.1.	Basic Formula.....	302
F.2.	Extended Formula	303
Appendix: G.	Calculation of Dependent Characteristics	305
G.1.	Background	305
G.1.1.	General.....	305
G.1.2.	Supported Characteristics.....	305
G.1.3.	Combination of Characteristic Types.....	305
G.1.4.	Execution Time	306
G.1.5.	Calculation Sequence	307
G.1.6.	Data Types	307
G.1.7.	Computation Methods.....	307
G.1.8.	Special functions for Dependent Characteristics	307
G.1.8.1.	Function min(x).....	307
G.1.8.2.	Function max(x).....	307
G.1.8.3.	Function interp(x,a [,b [,c [,d [,e]]]])	308
G.2.	Example	308
G.2.1.	Existing characteristics.....	308
G.2.1.1.	Arrays.....	308
G.2.1.2.	Curves.....	309
G.2.1.3.	Maps	310
G.2.1.4.	Scalars	310
G.2.2.	Dependent characteristics.....	311
G.2.3.	Example " Dependent Function interp()"	313
Index of Keywords and Enum Values		315
Figure Directory		318
Table Directory		319

Foreword

ASAM MCD-2 MC describes a data model for ECU Measurement and Calibration via a non XML format. Such data resides inside the memory of the ECU. The format definition makes the data accessible through application systems for tuning real-time testing. The description contains information about data types, dimensions, record layouts and memory locations of ECU variables. Further information describes how the variable values shall be converted into human-readable quantities and displayed in an MC-System.

In addition to the data description, the standard allows to describe the device interface between the MC-System and the ECU for read- and write access. As a result, the ASAM MCD-2 MC description contains all information in one place that is needed to access, modify, interpret and display ECU-internal variables.

The format definition describes the following content:

- A2L description file keywords
- AML format description
- AML template
- A2L and AML example