



ASAM

Association for Standardization of
Automation and Measuring Systems

ASAM ASAP 3

Automation Access Protocol for MC-Server

Part 1 of 1

Programmers Guide

Version 3.0.0

Date: 2019-01-20

Base Standard

© by ASAM e.V., 2019

Disclaimer

This document is the copyrighted property of ASAM e.V.
Any use is limited to the scope described in the license terms. The license
terms can be viewed at www.asam.net/license

Table of Contents

Foreword	6
1 Introduction	7
1.1 Overview	7
1.2 Motivation	8
1.3 Scope	8
2 Relations to Other Standards	9
2.1 Backward Compatibility to Earlier Releases	9
2.1.1 Parameter Scanning Time.....	9
2.1.2 Former State Diagram.....	9
2.2 References to Other Standards	9
3 Telegram structure	10
3.1 Data Types	10
3.1.1 ASAM Data Types.....	10
3.1.2 MC3 specific data type.....	11
3.1.2.1 MC3_STRING	11
3.1.3 Enumerations.....	11
3.1.3.1 A_UINT16 enumeration MC3_DATATYPE	11
3.1.3.2 A_UINT16 enumeration MC3_VALUETYPE	12
3.1.3.3 A_UINT16 enumeration CHAR_TYPE.....	12
3.2 Telegram Frame.....	13
3.3 Communication sequence	14
4 Command overview	16
4.1 ASAP3 Command Table.....	16
5 Detailed Description of all Commands	19
5.1 Common Commands	19
5.1.1 REPEAT REQUEST	19
5.2 Connecting and disconnecting between MC-Client and MC-Server	20
5.2.1 IDENTIFY	20
5.2.2 INIT	21
5.2.3 EMERGENCY	22
5.2.4 EXIT	23
5.3 Connecting between MC-Server and ECU	24
5.3.1 SWITCHING OFFLINE / ONLINE	24
5.4 Configuration.....	25
5.4.1 CHANGE BINARY FILE NAME.....	25
5.4.2 COPY BINARY FILE	26
5.4.3 DEFINE DESCRIPTION FILE AND BINARY FILE	27

5.4.4	SELECT DESCRIPTION FILE AND BINARY FILE	30
5.4.5	GET CALPAGE INFO	31
5.4.6	GET CHARACTERISTIC INFO	33
5.4.7	GET MEASUREMENT INFO	36
5.4.8	GET RASTER OVERVIEW	38
5.5	Measuring	40
5.5.1	GET ONLINE VALUE	40
5.5.2	GET ONLINE VALUE EV2	41
5.5.3	GET USER DEFINED VALUE	42
5.5.4	GET USER DEFINED VALUE LIST	43
5.5.5	PARAMETER FOR VALUE ACQUISITION	44
5.5.6	PARAMETER FOR VALUE ACQUISITION EV2	46
5.6	Recording	48
5.6.1	ACTIVATE RECORDER	48
5.6.2	DEFINE TRIGGER CONDITION	49
5.6.3	DEFINE RECORDER PARAMETERS	51
5.6.4	GET RECORDER RESULT DATA TYPES EV2	53
5.6.5	GET RECORDER RESULT HEADER	54
5.6.6	GET RECORDER RESULTS	56
5.6.7	GET RECORDER RESULTS EV2	57
5.6.8	GET RECORDER STATUS	59
5.6.9	LOAD RECORDER FILE	60
5.6.10	SAVE RECORDER FILE	61
5.7	Adjusting	62
5.7.1	GET CURRENT CALPAGE	62
5.7.2	GET LOOK-UP TABLE	63
5.7.3	GET LOOK-UP TABLE EV2	65
5.7.4	GET LOOK-UP TABLE VALUE	68
5.7.5	GET LOOK-UP TABLE VALUE EV2	69
5.7.6	GET PARAMETER	70
5.7.7	GET PARAMETER EV2	71
5.7.8	INCREASE LOOK-UP TABLE	73
5.7.9	INCREASE LOOK-UP TABLE EV2	74
5.7.10	PUT LOOK-UP TABLE	76
5.7.11	PUT LOOK-UP TABLE EV2	78
5.7.12	READ CHARACTERISTIC	81
5.7.13	READ CELL VALUES	84
5.7.14	SELECT LOOK-UP TABLE	87
5.7.15	SELECT LOOK-UP TABLE EV2	88
5.7.16	SET CURRENT CALPAGE	90
5.7.17	SET LOOK-UP TABLE	91
5.7.18	SET LOOK-UP TABLE EV2	92
5.7.19	SET PARAMETER	94
5.7.20	SET PARAMETER EV2	95
5.7.21	WRITE CHARACTERISTIC	96
5.7.22	WRITE CELL VALUES	99
5.8	Miscellaneous	102
5.8.1	SET CASE SENSITIVE LABELS	102
5.8.2	SET FORMAT	103
5.8.3	SET GRAPHIC MODE	105
5.8.4	RESET DEVICE	106

5.9 Container for MC-Server specific services	107
5.9.1 Introduction	107
5.9.2 EXECUTE SERVICE	108
5.9.3 GET SERVICE INFORMATION	109
5.9.4 QUERY AVAILABLE SERVICES	110
5.10 iLinkRT Configuration.....	111
5.10.1 SELECT CHARACTERISTIC.....	111
5.11 Error Handling	113
5.11.1 Status Codes	113
5.11.2 Error Codes.....	114
6 Terms and Definitions	123
7 Symbols and Abbreviated Terms	124
8 Bibliography	125
Appendix: A. Configuration of iLinkRT with ASAP3	126
A.1. Introduction	126
A.2. Architecture overview	126
A.2.1. Preconditions	126
A.2.2. Single MC-Client / Single MC-Server	126
A.2.3. Multi MC-Client / Single MC-Server with multiple iLinkRT Servers	127
A.2.4. Multi MC-Client / Multi MC-Server	128
A.3. ECU assignment.....	129
A.4. CHARACTERISTIC registration	129
A.5. MEASUREMENT registration.....	130
A.6. Activation of Configuration	130
A.7. De-Activation of Configuration.....	130
A.8. Example Sequence.....	130
Appendix: B. Control flow graph	131
B.1. General.....	131
B.2. Typical control flow.....	131
B.2.1. Setup	131
B.2.2. Calibration.....	133
B.2.3. Measurement.....	134
B.2.4. Recording	135
Figure Directory	136
Table Directory	137

Foreword

The ASAP3 standard continues to be a serial, command orientated, protocol communication between an MC-Client (e.g. Automation System (AuSy)) and an MC-Server (Measurement & Calibration Server).

The commands of the protocol support a single client system and allow realizing a synchronous communication for measurement and calibration.

As the lifetime of test benches is normally very high, it is necessary that existing applications continue to work even when parts are improved. To make it easy to adapt existing scripts to the new version, the compatibility to the former version is guaranteed.