

Association for Standardisation of Automation and Measuring Systems

ASAM MDF

Measurement Data Format

Version 4.1.1 Date: 2014-06-04

Base Standard

© by ASAM e.V., 2014

Disclaimer

This document is the copyrighted property of ASAM e.V. Any use is limited to the scope described in the license terms. The license terms can be viewed at <u>www.asam.net/license</u>



Table of Content

Foi	reword	6
<u>Ov</u>	erview	7
2.1	Intended Audience	7
2.2	Conventions	7
2.3	Abbreviations	7
2.4	Compliance to ASAM ODS Standard	8
<u>Inti</u>	oduction	9
<u>MD</u>	F Versions	11
4.1	Version History	11
4.2	Version Handling	12
4.3	Rules to Ensure MDF Compatibility between Versions	13
4.4	File Extension	16
<u>MD</u>	F General Block Format	17
5.1	Overview of Block Types Used	17
5.2	Definition of Data Types Used And Mapping to ASAM Data Types	19
5.3	General Block Setup	20
	5.3.2 Link section	20 20
	5.3.3 Data section	21
5 /	S.S.4 Description of Members	21
).4	5.4.1 String Encoding, Byte Order and Alignment	22
	5.4.2 Naming Rules	23
	5.4.4 Linking of Blocks	23 27
	5.4.5 Synchronization Domains	30
5.5	The File Identification Block IDBLOCK	32
	5.5.1 Block Structure of IDBLOCK 5.5.2 Unfinalized MDF	32 33
5.6	The Header Block HDBLOCK	37
	5.6.1 Block Structure of HDBLOCK 5.6.2 Contents of the Meta Data Block for the Header Comment	37 39
5.7	The Meta Data Block MDBLOCK	41
	5.7.1 Block Structure of MDBLOCK	41
5.8	5.8.1 Block Structure of TXBLOCK	42
5. <u>9</u>	The File History Block FHBLOCK	43
	5.9.1 Block Structure of FHBLOCK	43



5.9.2 Contents of the Meta Data Block for the File History Comment	44
 5.10 The Channel Hierarchy Block CHBLOCK 5.10.1 Block Structure of CHBLOCK 5.10.2 Contents of the Meta Data Block for the Hierarchy Comment 	45 45 48
 5.11 The Attachment Block ATBLOCK 5.11.1 Block Structure of ATBLOCK 5.11.2 Contents of the Meta Data Block for the Attachment Comment 	49 49 51
5.12 The Event Block EVBLOCK 5.12.1 Block structure of EVBLOCK 5.12.2 Common Use Cases for Events 5.12.3 Example For Events 5.12.4 Contents of the Meta Data Block for the Event Comment	51 52 59 60 62
 5.13 The Data Group Block DGBLOCK 5.13.1 Block Structure of DGBLOCK 5.13.2 Contents of the Meta Data Block for the Data Group Comment 	62 63 63
 5.14 The Channel Group Block CGBLOCK 5.14.1 Block Structure of CGBLOCK 5.14.2 Contents of the Meta Data Block for the Channel Group Comment 5.14.3 Variable Length Signal Data (VLSD) CGBLOCK 5.14.4 Example using a VLSD CGBLOCK 	64 64 67 67 68
 5.15 The Source Information Block SIBLOCK 5.15.1 Block Structure of SIBLOCK 5.15.2 Contents of the Meta Data Block for the Source Comment 	70 71 72
 5.16 The Channel Block CNBLOCK 5.16.1 Block Structure of CNBLOCK 5.16.2 Data Structure for Channel Data Type "CANopen Date" 5.16.3 Data Structure for Channel Data Type "CANopen Time" 5.16.4 Contents of the Meta Data Block for the Channel Comment 5.16.5 Contents of the Meta Data Block for the Channel Unit 	73 73 84 84 85 85
 5.17 The Channel Conversion Block CCBLOCK 5.17.1 Block Structure of CCBLOCK 5.17.2 CCBLOCK – 1:1 Conversion 5.17.3 CCBLOCK – Linear Conversion 5.17.4 CCBLOCK - Rational conversion 5.17.5 CCBLOCK – Algebraic Conversion (MCD-2 MC Text formula) 5.17.6 CCBLOCK – Value to Value Table With Interpolation 5.17.7 CCBLOCK – Value to Value Table Without Interpolation 5.17.8 CCBLOCK – Value Range to Value Table 5.17.10 CCBLOCK – Value Range to Text / Scale Conversion Table 5.17.11 CCBLOCK – Text To Value Table 5.17.12 CCBLOCK – Text To Text Table 5.17.13 Contents of the Meta Data Block for the Conversion Comment 5.17.14 Contents of the Meta Data Block for the Conversion Unit 	88 91 92 93 93 93 94 95 96 97 99 100 101
5.18 Composition of Channels 5.18.1 Structures 5.18.2 Arrays	102 102 105
5.19 The Channel Array Block CABLOCK 5.19.1 Block structure of CABLOCK	105 105



5.	20 Nested Composition of Channels	120		
	5.20.1 Structures of Composed Signals 5.20.2 Arrays of Composed Signals	120		
5.	21 The Data Block DTBLOCK	126		
	5.21.1 Block structure of DTBLOCK	126		
	5.21.2 Data Block Format	126		
	5.21.4 Reading Signal Values from a Data Record	120		
	5.21.4.1 Reading the Invalidation Bit	129		
	5.21.4.2 Reading the Signal Value	130		
	5.21.6 Example 2: Big Endian (Motorola) Byte Order	132		
5.	22 The Sample Reduction Block SRBLOCK	133		
	5.22.1 Block Structure of SRBLOCK	133		
	5.22.3 Layout of Sample Reduction Records	134		
5.	23 The Reduction Data Block RDBLOCK	137		
	5.23.1 Block structure of RDBLOCK	137		
5.	.24 The Signal Data Block SDBLOCK	137		
	5.24.1 Block structure of SDBLOCK 5.24.2 Example for Usage of SDBLOCK	130		
5	25 The Data List Block DI BLOCK	140		
01	5.25.1 Block structure of DLBLOCK	140		
5.	26 The Data Zipped Block DZBLOCK	144		
	5.26.1 Block structure of DZBLOCK 5.26.2 Transposition of Data	145 146		
5.	.27 The Header List Block HLBLOCK	148		
	5.27.1 Block structure of HLBLOCK	148		
<u>6</u> <u>M</u>	IDF Meta Data Format	150		
6.	1 Content of the MDBLOCK	150		
	6.1.1 XML Versioning	150		
	6.1.2 Standard Lags 6.1.3 Standard Attributes	151 152		
	6.1.4 Embedding of Markup	152		
6.	2 Common Properties	153		
	6.2.1 <e> Tag</e>	153		
	6.2.2 <tree> lag 6.2.3 <list> Tag</list></tree>	154 155		
	6.2.4 <elist> Tag</elist>	156		
6.	3 Vendor Extensions	156		
6.	4 Alternative Names	157		
6.	5 Formula Specifications	157		
Figuredirectory				
Tabledirectory				
Bibliog	Bibliography and References 16			



1 FOREWORD

MDF stands for Measurement Data Format. It is a binary file format to store measured or calculated data for post-measurement processing or long-term conservation. Common sources of the data to be stored are sensors, ECUs or bus monitoring systems. In addition to the plain measurement data, MDF also contains descriptive and customizable meta data within the same file.

The format is organized in loosely coupled binary blocks to ensure high performance reading and writing. The measurement data is stored channel-oriented and organized in records. MDF supports non-equidistant sampling rates and multiple rates per file. Master channels are used for synchronization which can be time, angle, distance or simply index related.

MDF allows storage of raw measurement values and corresponding conversion formulas. It supports special data types and information particularly required in the automotive area, and is closely related to other ASAM standards, e.g. ASAM MCD-2 MC (ASAP2).

The format definition is published in the base standard which describes the following content:

- Version history
- Version handling and compatibility rules
- MDF block structure
- General rules
- List of all binary block types and their contents
- MDF meta data format (XML)

The description how to store information for certain use cases is published in different associated standards. Such use cases are:

- Naming of Channels and Channel Groups [MDF-NC] This associated standard describes how to set the different names for channels and channel groups for common use cases in order to provide important information to the user and to achieve a unique identification of the channels.
- **Bus Logging** [MDF-BL] This associated standard describes how to store the traffic of common bus systems.
- **Measurement Environment** [MDF-ME] This associated standard describes how to store information about the measurement environment.

Binary example MDF files are contained in the deliverable of the respective standard or may be requested from the ASAM COMMON MDF working group (mdf@asam.net).